# LONGLIFE complete Ultra-performance floor polish

# Sustainability Information

# **Sustainable Contribution**

- Developed to fulfill the Austrian Ecolabel
- Registered in the positive list of ,DIE UMWELTBERATUNG'
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration
- With surfactants of renewable plant-based origin



### **Quality & Performance**

- More than 30 years of experience in the development of high-performance and integrally sustainable cleaning concepts.
- Our Green Care Professional products are produced exclusively in the EMAScertified plants in Mainz and Hallein in compliance with the highest quality standards



### Safe for humans & environment

- Our formulas and packaging are safe for humans and nature as well as biological and technical cycles when used properly
- LONGLIFE complete is formulated from readily biodegradable raw materials

# **Circular cleaning products**

- Production with intensive use of renewable raw materials and energy up to 100% from hydropower, solar and geothermal power
- To find out how much plastic, CO<sup>2</sup> and crude oil can be saved with Green Care Professional products, visit: get.wmprof.com



# Sustainable profitability

- Our intelligent systems and efficient formulas enable precise and eco nomical dosing as well as complete emptying of the packaging
- Comprehensive and consistently practiced philosophy of sustainable management

# **Comprehensive Service**

- As a strategic partner, we offer comprehensive know-how transfer through holistic consulting and support as part of our Green Care Academy
- Customized hygiene plans and cleaning recommendations optimizing your cleaning procedures and thus your business

# Product certificates



### Company certificates of Management Systems



**EMAS**: Most demanding system for sustainable environmental



**DIN ISO 14001**: Internationally recognized environmental management system

(R)



**DIN ISO 50001**: Internationally recognized energy management system



**DIN ISO 9001**: Internationally recognized quality management system



**EcoVadis**: Provider of business sustainability ratings

# LONGLIFE complete

# Ultra-performance floor polish

Complete economy |Complete safety |Complete flexibility

# **Product profile**

- LONGLIFE complete provides the complete solution for highest standards in coating of hard and elastic floors combined with exceptional environmental properties.
- Meanwhile enhancing the work safety, LONGLIFE complete assures outstanding durability and resistibility even against alcohol and skin disinfectants as well as a long-life pleasant appearance and gloss.
- LONGLIFE complete is completely user safe due to its time-saving processability even on damp linoleum floors, its reduced slip hazard whilst stripping and its easy-to-use features. Its certification according DIN 18032-2 proves outstanding slip resistance.
- LONGLIFE complete is as flexible as an elastic coating, extremely adhesive and elastic and therefore, suitable for elastomer (rubber) flooring and areas with high point load.
- This product works ideally in a system with LINAX complete, which easily removes even multilayer LONGLIFE complete polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP and fluorinated levelling agents, LONGLIFE complete takes on the responsibility for future generations.

# Area of application

- LONGLIFE complete is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- Specially recommended for highly frequented areas, e.g. hospitals, schools, retail markets, airports, entrance areas etc. where high durability and long life cycle of coating is required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.

# Ingredients, handling, storage and environmental instructions

For the ingredients list, please see the Safety Data Sheet. Product strictly reserve for a professional use. For all information regarding handling, storage conditions and disposal, please see the Safety Data Sheet.

# **Product variants**

1112513 - 2x 5 l






# **Application and Dosing**



Dose in relation to application. Follow below instructions.

#### Floor preparation:





Initial treatment: Apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.

### Large areas:

Work in sections and apply wet in wet. Usage: approx.  $2l / 100 m^2$ .

### 200 ml/l



**Coating refreshment:** Remove slight scratches using

the spray-cleaner-method and a highspeed machine with red pad.

Learn more at: www.green-care-academy.com