

Sustainable Contribution

• Developed to fulfill the Austrian Ecolabel

- Registered in the positive list of ,DIE UMWELTBERATUNG'
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration
- With surfactants of renewable plant-based origin
- LONGLIFE complete with all its ingredients is totally biodegradable and has proven this important property in an accredited mineralization test according to OECD 302 B standard



Quality & Performance

- More than 30 years of experience in the development of high-performance and integrally sustainable cleaning concepts.
- Our Green Care Professional products are produced exclusively in the EMAScertified plants in Mainz and Hallein in compliance with the highest quality standards



Safe for humans & environment

- Our formulas and packaging are safe for humans and nature as well as biological and technical cycles when used properly
- LONGLIFE complete is formulated from readily biodegradable raw materials



Circular cleaning products

- Production with intensive use of renewable raw materials and energy up to 100% from hydropower, solar and geothermal power
- To find out how much plastic, CO² and crude oil can be saved with Green Care Professional products, visit: get.wmprof.com



Sustainable profitability

- Our intelligent systems and efficient formulas enable precise and economical dosing as well as complete emptying of the packaging
- Comprehensive and consistently practiced philosophy of sustainable management



Comprehensive Service

- As a strategic partner, we offer comprehensive know-how transfer through holistic consulting and support as part of our Green Care Academy
- Customized hygiene plans and cleaning recommendations optimizing your cleaning procedures and thus your business

Product certificates





Company certificates of Management Systems



EMAS: Most demanding system for sustainable environmental



DIN ISO 14001: Internationally recognized environmental management system



DIN ISO 50001: Internationally recognized energy management system



DIN ISO 9001: Internationally recognized quality management system



EcoVadis: Provider of business sustainability ratings

LONGLIFE complete

Ultra-performance floor polish

Complete economy | Complete safety | Complete flexibility

Product profile

- LONGLIFE complete provides the complete solution for highest standards in coating of hard and elastic floors combined with exceptional environmental properties.
- Meanwhile enhancing the work safety, LONGLIFE complete assures outstanding durability
 and resistibility even against alcohol and skin disinfectants as well as a long-life pleasant
 appearance and gloss.
- LONGLIFE complete is completely user safe due to its time-saving processability even on damp linoleum floors, its reduced slip hazard whilst stripping and its easy-to-use features. Its certification according DIN 18032-2 proves outstanding slip resistance.
- LONGLIFE complete is as flexible as an elastic coating, extremely adhesive and elastic and therefore, suitable for elastomer (rubber) flooring and areas with high point load.
- This product works ideally in a system with LINAX complete, which easily removes even multi-layer LONGLIFE complete polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP and fluorinated levelling agents, LONGLIFE complete takes on the responsibility for future generations.

Area of application

- LONGLIFE complete is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- Specially recommended for highly frequented areas, e.g. hospitals, schools, retail markets, airports, entrance areas etc. where high durability and long life cycle of coating is required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.

Ingredients, handling, storage and environmental instructions

For the ingredients list, please see the Safety Data Sheet. Product strictly reserve for a professional use. For all information regarding handling, storage conditions and disposal, please see the Safety Data Sheet.

Sales units:

1112513 - 2 X 5 l



pH value



8



Application and Dosing



Dose in relation to application. Follow below instructions.



Floor preparation

Strip the floor, remove all dirt and old dispersion layers.



concentrated

Initial treatment

Apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.



Large areas

Work in sections and apply wet in wet. Usage: approx. 2l / 100 m²



200 ml/l

Coating refreshment

Remove slight scratches using the spray-cleaner-method and a highspeed machine with red

Learn more at: www.green-care-academy.com