



Technical Information

Product profile

- GREASE speed is easy to use and removes easily oil and greasy residues on all water and alkaline resistant surfaces.
- GREASE speed is pleasant in practice thanks to its perfume and dye free recipe.
- GREASE speed enables to save time by being applied manually and mechanically.
- Despite outstanding emulsifying ability of grease and oil, fast separation in grease-oilseparator (Ö-Norm 5105).

Area of application

- Suitable for all canteens and food processing industries.
- GREASE speed was especially designed for industrial kitchens, restaurants, hotels, canteens and catering services.
- Applicable in food processing areas on stainless steel, glass, tiles, stone, plastics, etc. and useable on floors, grills and stoves, walls, counters, etc.
- Not suitable for aluminium, enamel and non-alkaline consistent surfaces.

Ingredients, handling, storage and environmental instructions

For the ingredients list, please see the Safety Data Sheet. Product strictly reserved for a professional use. For all information regarding handling, storage conditions and disposal, please see the Safety Data Sheet.

Product variants

712697 - 10X 1 l **1209686** - 1 X 10 l

Company certificates of Management Systems













pH value



Application and Dosing



Dose in relation to application and degree of water hardness. Follow below instructions.



20-50 ml/l

Pre-soaking:

Pre-soak dishes between 10 and 15 minutes.



20-100 ml/l

Spray bottle:

Spray directly or onto a suitable cloth and wipe the surface.



20-30 ml/l

Powerful cleaning:

Also applicable in the tana cleaning & hygiene station.



concentrated & 10-100 ml/l

Manual application:

Can be used in warm & steam ovens or grills.

