

# ENERGY turbo



## Sustainable development and production



### EMAS:

- Continuous improvement of environmental performance
- Annual sustainability report
- Energy and water management
- Social Fairness



### DIN ISO 14001:

- Continuous improvement in reducing waste and CO2 emissions, and saving of energy, water and material consumption



### ISO 50001:

- Continuous improvement of energy management: performance, efficiency, security, use and consumption



### A.I.S.E.-Charter:

- Safe and sustainable manufacturing of cleaning products



### DIN ISO 9001:

- Continuous improvement of management processes and customer satisfaction
- Established quality management system in product development and production

## **green-Effective® High alkaline detergent for professional dishwashers**

### ■ Eco-efficient performance with eco-effective product design

User and environmental safety at the highest cleaning performance



- Certified with the European Ecolabel (AT/038/005)
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration

### Complete biodegradability



- ENERGY turbo with all its ingredients is totally biodegradable and has proven this important property in an accredited mineralization test according to OECD 302 B standard\*

\*for more information please visit [www.wmprof.com](http://www.wmprof.com)

### Intensive use of renewable resources – continuous increase of the reutilisation score



- Production under extensive use of renewable raw materials and energy using to 100% hydroelectric, solar and geothermic power
- Production widely independent of crude oil: 49% of organic carbon processed in ENERGY turbo originates from renewable plant resources which enables a production that is widely independent of crude oil
- Active water stewardship maintaining an own fresh and waste water treatment

### Ingredient declaration

For the ingredients list, please see the Safety Data Sheet

### Traditional German quality - driving your durable business development



- More than 30 years pioneer in sustainable product development
- Smart hygiene solutions ensuring profitable growth
- Trusted brand

### Professional user training and on-site support for Sustainable Hygiene Solutions



- Comprehensive knowledge transfer through qualified cleaning consultants
- Customized hygiene plans and cleaning recommendations optimizing your business and cleaning procedures
- Increased service value and strengthened company reputation



# ENERGY turbo



## **green-Effective® High alkaline detergent for professional dishwashers**

- 3-in-1 ■ Highly concentrated ■ Outstanding result

### Product profile

- ENERGY turbo is a concentrated, innovative and high performing formulation without EDTA, NTA or phosphate complying with highest environmental standards.
- ENERGY turbo removes even very persistent food residues and is versatile for excellent and uniform results.
- ENERGY turbo is efficient and works quickly, therefore it allows to save costs and time.
- ENERGY turbo enables a quick reuse of dishes, increases work efficiency and is a universal product for easier working processes.

### Area of application

- ENERGY turbo can be used as machine-dish-cleaner in all tank and multi-tank machines or as cleaning intensifier.
- Ideal for use in soft and middle hard water.
- ENERGY turbo use for pre-soaking: Carefully place dishes in lukewarm water, so that everything is completely covered. Max. heat 40°C. Depending on degree of soiling leave to soak for 10-20 minutes. After removing dishes from pre-cleaning or soaking solution go on with cleaning in the usual way.

### Product safety, storage and environmental instructions

**Safety:** For professional use only. For further information, see Safety Data Sheet. For maximum effectiveness always use the correct dosage and lowest recommended temperature. This will minimize both energy and water consumption and reduce water pollution.

**Storage:** Store at room temperature in the original container.

**Environmental:** Only give completely emptied packaging to special waste disposer.

### Application and Dosing



Dose in relation to application and degree of soil. Follow below instructions.



for heavy soiling.

5-10 g/L



**Pre-soaking:** Put dishes in luke warm water—max 40°C. Soaking time: 10–20 min.

0.8-3 g/L



automatic dosing systems highly recommended.

0.5-2 g/L



**Boosting application:** dosing recommendation when applied as booster.



Put the dishes in an upright position and let them drip dry.



**Precaution:** wear suitable protective clothing, gloves and eye protection.

### Sales units

Order No. 715514 1 x 10 L  
Order No. 716916 1 x 200L

### Your trusted partner on site

pH-Value 1 %

