

# LOGLIFE diamond



## Long-lasting, high gloss emulsion polish

- Long-lasting ■ High gloss ■ Easy application

### Product profile

- LONGLIFE diamond is a high gloss and resistant emulsion polish which protects the flooring and is wear and tear resistant.
- The time- and cost-saving LONGLIFE diamond is recommended wherever an excellent look or a durability of the protection film is desired.
- As a safety aspect LONGLIFE diamond is slip-resistant because of the contained powerful care components (according to DIN 51131) even under strong frequentation.
- LONGLIFE diamond with its uniform look is highly resistant to heel marks and soils even during highest strains.
- The high-speed-polishing increases the durability and furthermore it reduces resoiling and enables lasting cleanness.
- LONGLIFE diamond is fast and simple in the processing, shows an excellent flow and an appealing high gloss.

### Area of application

- LONGLIFE diamond belongs to the hard/strong, extremely durable polymer dispersions and is very suitable for the maintenance of PVC, linoleum, specific plastic coverings etc.
- Do not apply on unsealed wood and polished stone floors.

### Ingredient declaration

For the ingredients list, please see the Safety Data Sheet

### Sustainable development and production



### Product safety, storage and environmental instructions

**Safety:** For professional use only. For further information see Safety Data Sheet.

**Storage:** Store at room temperature in the original container. Keep from freezing.

**Environmental:** Only give completely emptied packaging to a special waste disposer.


### Application and Dosing



Dose in relation to application. Follow below instructions.



**Floor preparation:** strip the floor, remove all dirt and old dispersion layers.




concentrated

**Initial treatment:** apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.



**Large areas:** work in sections and apply wet in wet. Usage: approx. 2 L / 100 m<sup>2</sup>.



200 mL/L

**Coating refreshment:** remove slight scratches using the spray-cleaner-method and a highspeed machine with red pad.



After awaiting the fair drying time (one day) polish with Ultra High-Speed-Method (>1000 U).

### Sales units

Order No. 702632 1 x 10 L

### Your trusted partner on site

pH-Value

